

LIGHTING FIXTURE REVISIONS; Rev: 7.25.14

1. Move Wall Sconces in Entry to be 8" o.c. from opening into Living room.
  2. Wall Sconces in Living to be 6" o.c. from rough opening of Exterior French Doors.
  3. Wall Sconces just inside Living, adjacent to 10' wide arch to be centered on wall segments.
  4. At West Bedroom Hallway, provide two (2) Cree ESA-ADR-4-14-LWW-WF-12-27K, wall washers to be aimed at north 8'-6" wall segment, o.c. with eye level, i.e. 5'-6" height + or -. Control with a Dimmer.
  5. Center Entry light fixture between truss and wall to the Living room.
  6. Note Change in location of Door No. 15 from Hallway to Bedroom 3.
  7. 6" recessed light fixture removed from end of hallway outside Bedroom 3.
  8. Three (3) ceiling mounted light fixtures replace four (4) wall mounted light fixtures in west bedroom Hallway.
  9. Game room, mount Pool Table ceiling light fixture 9'-2-1/2" from north wall finish, and 6'-3" from east wall finish.
  10. At Dining room, provide two (2) ceiling mounted lighting fixtures over Dining room table to be 6'-0" o.c. in center of Dining room.
- Rev. 8.26.14
11. Provide three (3) lighting fixtures over Kitchen Island at 2'-6" o.c. ceiling mounted, centered over the island.
  12. At Hallway to Garage, one ceiling mounted light fixture replaces two ceiling recessed fixtures.
  13. At Hallway to Bedroom 4, one ceiling mounted light fixture replaces one wall mounted light fixture.
  14. All Dimmers shall support LED type lighting fixtures, even if those fixtures were originally designed to be lamped with incandescent bulbs.
  15. Add Recessed light fixture in Laundry over sink.

- Rev. 9.12.14
16. Relocate Fountain from the entry court out to the driveway, centered on the entry. See Sheet No.11 for dimension to the building. Provide 1 inch diameter sch. 80 conduit with power for lighting and small pump at the fountain.
  17. Provide additional recessed light fixture at Bath 5.
  18. At Laundry, omit under cabinet light fixture over washer and dryer.
  19. Provide an additional recessed light fixture in Pantry.
  20. At A/V Equipment cabinets in Family room, omit under cabinet light fixture.
  21. At Dining room, omit one of the wall mounted light fixtures on north wall.
  22. Omit light fixtures at south patio, but retain switching leg with 3/4 inch conduit to edge of Verandah.
  23. Omit one ceiling recessed light fixture at the Office.
  24. Omit wall mounted light fixture at south wall M.Bath WC.
  25. Omit wall mounted light fixture at west wall Bath 3.
  26. See Site Plan Sheet No. 2 for the location of Driveway lights and provide switched leg for two (2) Driveway Entry light fixtures ( same circuit as driveway lights), and power for Entry Gate.

Electrical Lighting Plan